

WYLER PRODUCTS AND SERVICES

WYLER-PRODUKTE UND -SERVICES



WYLER AG
Inclination measuring systems
Neigungsmesssysteme

Version 2025
Edition 1

Im Hölderli 13, CH - 8405 Winterthur (Switzerland)
+41 52 233 66 66
wyler@wylerag.com
www.wylerag.com



INTRODUCTION

SPIRIT LEVEL

EINFÜHRUNG

WYLER Spirit Levels have been known for decades all around the globe for their high precision, quality and reliability. All products are manufactured according to the relevant international standards and assure an extraordinary resistance against wear and geometrical deformation due to the use of selected and well matured materials.

The **SPIRIT LEVELS** are divided into the following types:

Spirit levels for small angles



Clinometers for large angles up to 360°



Most spirit levels can be equipped with magnetic inserts. Magnetic inserts do not guarantee a secure hold, they are only to be regarded as a support when holding. Please secure your measuring instruments from falling at all times to avoid damage and injuries.


Besides the vial, the frame or body of a precision level is extremely important. The material mostly from cast iron or special steel must be free from tension (distortion!). The treatment of the material before, during and after the machining and assembling is of greatest importance. Blowholes up to a diameter of 0.5 mm outside the measuring surfaces do not constitute a defect.

Usually, the bases of the levels for measuring surfaces have two contact faces. These allow the exact setting of the instrument. Prismatic bases with two contact faces are used for measuring round shafts and bars. A speciality of the WYLER precision levels lies in the fact that the geometry of the bases is adjusted exactly parallel to the vial axis by grinding and scraping.

Only by this precision work it is assured that even when the level is slightly tilted no measuring error occurs (twist stability). The specialist is aware of the temperature sensitivity of a spirit level. Therefore no direct sunlight is allowed on the level and draught is avoided, if a precise measurement is to be guaranteed.



The user has the possibility to adjust the **ZERO** as well as the **TWIST** thanks to a simple adjustment system



Products may differ from the pictorial representation.
For current specifications, please refer to the separate data sheet

Operating temperature range
Storage temperature range

15 ... + 25°C
- 40 ... + 70 °C


Betriebstemperatur
Lagertemperatur

Produkte können von der bildlichen Darstellung abweichen.
Aktuelle Spezifikationen entnehmen Sie dem separaten Datenblatt.

Standard dimensions of prismatic bases

Standardabmessungen prismatischer Basen

Length of base Basislänge	Possible shaft diameter Messbarer Wellendurchmesser		
L / mm	A / mm	B / mm	Ø / mm
100	30	21	17 ... 80
100	32	22	17 ... 84
150	35	24.5	17 ... 94
200	40	28	19 ... 108
250	45	31.5	19 ... 120
300	50	35	22 ... 135



INTRODUCTION	PRODUCT RANGE	EINFÜHRUNG
--------------	---------------	------------



SCREW-ON SPIRIT LEVEL

66

AUF SCHRAUB-RICHTWAAGE

SWISS MADE**General**

- According to DIN877 + DIN2276/1
- Flat measuring base, not recessed in the middle part
- The vial is firmly sealed in a stable steel body of cubic shape, outside gun-blued

Allgemein

- Gemäss DIN877 + DIN2276/1
- Durchgehende flache Messbasis
- Die Libelle ist in ein stabiles, brüniertes Vierkant-Stahlprofil eingegossen

Application

- The Screw-on spirit level 66 is suitable for measurements on horizontal surfaces of machines, apparatus, etc. as well as for permanent mounting on measuring objects

Anwendung

- Die Aufschraub-Richtwaage 66 eignet sich hervorragend für das Messen von horizontalen Flächen an Maschinen und Apparaten, usw. sowie für die permanente Installation an Messobjekten

Length Länge	Width Breite	Height Höhe	Weight (gross) Gewicht (brutto)	Hole center distance Lochabstand	Screws Schrauben	Scale division value Skalenteilungswert	From stock Ab Lager	P/N Produktnummer
/ mm	/ mm	/ mm	/ kg	/ mm		/ (mm/m)		
30	10	10	0.015	25	M2	2-5		166-030-121,002
40	10	11	0.025	35	M2	2-5		166-040-121,002
50	10	12	0.03	40	M2	1.0	X	166-050-121,001
60	12	14	0.05	50	M3	0.30	X	166-060-121-300
						1.0		166-060-121,001
						2-5	X	166-060-121,002
80	15	18	0.10	70	M4	0.10		166-080-121-100
						0.30	X	166-080-121-300
						1.0		166-080-121,001
100	18	22	0.20	86	M4	0.10	X	166-100-121-100
						0.30	X	166-100-121-300
						1.0		166-100-121,001
120	18	22	0.25	105	M4	0.10		166-120-121-100
						0.30		166-120-121-300
150	18	22	0.30	135	M4	0.10		166-150-121-100
						0.30		166-150-121-300
						1.0		166-150-121,001

Scope of delivery	P/N Produktnummer	Lieferumfang
Screw-on spirit level 66	See above / Siehe oben	Aufschraub-Richtwaage 66
Calibration certificate	P/N	Kalibrierzertifikat
SCS calibration certificate for Screw-on spirit level 66	SCS WW-H	SCS-Kalibrierzertifikat für Aufschraub-Richtwaage 66

Quality**Qualität****Service + Partnership****Service + Partnerschaft****Innovation + Competence****Innovation + Kompetenz****Innovation****Quality****Service****WYLER**

The WYLER AG is continuously enhancing their products and reserves the right to change technical specifications as well as the appearance without prior notice. For this reason the specifications and the pictures of the products delivered may be slightly different from those shown in the catalogue.

Die WYLER AG ist stets um Produkteverbesserungen bemüht und behält sich das Recht vor, die technischen Daten und das äußere Erscheinungsbild jederzeit und ohne Vorankündigung zu ändern. Aus diesem Grund können die Spezifikationen und die Abbildungen der Produkte zum Teil leicht vom Katalog abweichen.